

DIGITUS Network Rack Dynamic Basic Series - 800x800 mm (WxD)

DN-19 42U-8/8-D
EAN 4016032336525



42U network rack, Dynamic Basic 2040x800x800 mm, color grey (RAL 7035)

The Racks of the Dynamic Basic Series were designed for the user friendly installation of active- and passive network components accompanied by a neat cable management. Each rack consists of up to 1.5 mm strong steel sheet material which ensures a very good stability as a robust steel construction due to special plate curving technique. The color is created by powder coating in grey (RAL 7035) and black (RAL 9005). For certain conditions, where the set-up location is difficult to reach, the rack can be disassembled. Doors can be easily detached and the door stop can be changed from right to left. Furthermore the roof is ready for the mounting of an air ventilation unit. Each rack contains 2 pairs (4 pieces) of 483 mm (19") profile rails inside which are galvanized and with height unit marking (countable from both directions). They are variable in depth and connected with additional depth support bars to realize extensive 483 mm (19") equipment installations. An important aspect for each installation is the cable management. The base of each rack is equipped with a punched out cable entry covered with a metal plate, whereas the base of 800 mm width racks gets extended with additional punched out cable entries with plastic covers left and right. These are also placed in the roof (1x for 600 mm width cabinets, 3x for cabinets from 800 mm width. An extensive portfolio of accessories for cable management, shelves, etc. will help to meet many requirements in daily use.

The DIGITUS® Dynamic Basic Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Lateral metal struts front door with safety glass
- Lock system with pivot lever on front door

- 120° door opening angle on the front door
- 1-point-locking-mechanism on the front door
- Rear wall and side panels are lockable and detachable
- incl. 4 pieces of leveling feet already pre-configured under the rack
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Base with punched out cable entry, covered with screwed metal plate
- Base with punched out cable entries with plastic covers left and right
- Roof with punched out cable entries with plastic covers
- Roof is prepared for fan units (punched out entries)
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Equipment mounting depth min.-max.: 430-750 mm
- Equipment mounting depth min.-max.: 430-750 mm
- Rack is completely mounted
- IP protection class: IP20
- Color: light grey, RAL 7035
- Depth: 800 mm
- Front door: Glass door, single opening
- Units: 42
- Load capacity: 600 kg
- Mounted: yes
- Rear door: Steel door, closed, single opening
- Side panels: Both sides
- Cabinet type: Network cabinet
- Width: 800 mm

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	112.50	88.00	88.00	220.00	1,703,680.00
Packaging Unit Inside	1	112.50	88.00	88.00	220.00	1,703,680.00
Packaging Unit Single	1	112.50	88.00	88.00	220.00	1,703,680.00
Net single without Packaging	1	109.48	88.00	88.00	220.00	1,703,680.00

More images:

